

29.01.2025

DECLARATION OF CONFORMITY Nr. 2025-01

The following products are manufactured from construction steel S235, with a minimum yield strength 235 MPa and a minimum tensile strength 370 MPa. Hot-dip galvanizing with a minimum of 50 µm.

U-type

- 73501** Post foot U-type 50x40
- 73502** Post foot U-type 50x60
- 73503** Post foot U-type 75x40
- 73504** Post foot U-type 75x60
- 73506** Post foot U-type 90x90
- 73507** Post foot U-type 100x40
- 73508** Post foot U-type 100x60
- 73509** Post foot U-type 100x90
- 73511** Post foot U-type 120x70
- 73512** Post foot U-type 120x90
- 73513** Post foot U-type 125x90
- 73514** Post foot U-type 150x60
- 73520** Post foot U-type 140x90
- 73525** Post foot U-type 45x40
- 73527** Post foot U-type 48x40
- 73535** Post foot U-type 80x60
- 73551** Post foot U-type 90x90
- 73552** Post foot U-type 100x70

U-type STRONG

- 73531** Post foot U-type 50x40
- 73532** Post foot U-type 100x60

L-type

- 73515** Post foot L-type 70x60
- 73524** Post foot L-type 84x90

I-type

- 73516** Post foot I-type 90x60

Adjustable

- 73517** Post foot, adjust. 70-120
- 73522** Post foot, adjust. 80-160
- 73519** Post foot adjust. 90-150, adjust. leg 240-290
- 73523** Post foot adjust. 70-105, adjust. leg 240-290
- 73518** Post foot adjust. 105-160 with sole (leg 115-185)
- 73521** Post foot adjust. 80-120 with sole (leg 115-165)
- 73553** Post foot adjust. 80-100 with sole (leg 115-165)
- 73554** Post foot adjust. 80-110 with sole (leg 115-165)

With ground plate

- 73801** Post foot 50x50 l=150 with ground plate, type B
- 73802** Post foot 50x100 l=150 with ground plate, type B
- 73803** Post foot 75x75 l=150 with ground plate, type B
- 73804** Post foot 90x90 l=150 with ground plate, type B
- 73805** Post foot 100x100 l=150 with ground plate, type B
- 73806** Post foot 120x120 l=150 with ground plate, type B
- 73807** Post foot 140x140 l=200 with ground plate, type B

Screwpost

- 73933** Screwpost 50x70x125 screw-in, L=800, d=50
- 73934** Screwpost 90x70x125 screw-in, L=1000, d=70
- 73935** Screwpost 100x70x125 screw-in, L=1000, d=70
- 73936** Screwpost 100x70x125 screw-in, L=1200, d=70
- 73937** Screwpost 100x100 screw-in, L=1200, d=92
- 73938** Screwpost 100x100 screw-in, L=1400, d=92

Drive-in

- 73901** Drive-in post support 50x50mm, L=600mm, type A
- 73902** Drive-in post support 50x100mm L=750mm, type A
- 73903** Drive-in post support 75x75mm, L=750mm, type A
- 73904** Drive-in post support 100x100mm, L=750mm, type A
- 73905** Drive-in post support 90x90mm, L=750mm, type A
- 73906** Drive-in post support 95x95mm, L=750mm, type A
- 73911** Circular drive-in post support 80mm, L=750mm, type A
- 73912** Circular drive-in post support 100mm, L=750, type A

Screw-in

- 73915** Screw-in post support 50x50, L=650mm
- 73916** Screw-in post support 100x100, L=750mm
- 73931** Post foot 70-105 adjust. /screw-in L=750mm

The following products are manufactured from construction steel S235, with a minimum yield strength 235 MPa and a minimum tensile strength 370 MPa. Zinc coating thickness: 5-8 µm.

Threaded column shoe

74001 Threaded column shoe 50x50x5,0 M10x150

74002 Threaded column shoe 60x60x4,0 M16x120

74003 Threaded column shoe 100x70x8,0 M20x150

74004 Threaded column shoe 100x100x8,0 M30x200

74007 Threaded column shoe 100x100x8,0 M24x200

Signed on behalf of the distributor by:



Kristi Voorel
Quality Manager