

04.04.2025

DECLARATION OF CONFORMITY Nr. 2025–06

The following products are manufactured of steel Q195 with a minimum tensile strength of 410 MPa.

Coating: annealed

- 85001** Straight wire 1,2x400 5kg
- 85004** Straight wire 1,2x500 5kg
- 85011** Straight wire 0,9x400 5kg
- 85130** Loop tie wire 1,2x100mm (1000pcs)
- 85131** Loop tie wire 1,2x120mm (1000pcs)
- 85132** Loop tie wire 1,2x140mm (1000pcs)

Coating: plastic

- 85121** Florist wire 0,65mm x ca40m/ ca100g green

Coating: zinc, 4-6 µm.

- 85002** Straight wire 1,2x400 Zn 5kg
- 85006** Straight wire 1,2x450 Zn 5kg
- 85009** Straight wire 1,2x550 Zn 5kg
- 85107** Wire 0,7mm Zn 50m
- 85108** Wire 1,0mm Zn 50m
- 85109** Wire 1,250mm Zn 25m
- 85122** Florist wire 0,7mm x ca35m/ ca100g Zn
- 85134** Loop tie wire 1,2x100mm Zn (1000pcs)

85135 Loop tie wire 1,2x120mm Zn (1000pcs)

85136 Loop tie wire 1,2x140mm Zn (1000pcs)

85137 Loop tie wire 1,2x180mm Zn (1000pcs)

Coating: copper, 4-6 µm.

85003 Straight wire 1,2x400 Cu 5kg

85005 Straight wire 1,2x550 Cu 5kg

85010 Straight wire 1,2x450 Cu 5kg

Coating: hot-dip galvanized, approx. 50-60 g/m².

85101 Wire 1,2mm 5kg HDG ca560m

85102 Wire 2mm 5kg HDG ca203m

85103 Wire 2,5mm 5kg HDG ca129m

85104 Wire 3mm 5kg HDG ca91m

85105 Wire 4mm 5kg HDG ca51m

85106 Wire 5mm 5kg HDG ca32m

The following products are manufactured of stainless steel AISI 304.

85008 Straight wire 0,9x400 stainless 5kg

Signed on behalf of the distributor by:



Henry-Stiven Villem
CEO