

24.09.2025

DECLARATION OF CONFORMITY Nr. 2025-27

The following products are manufactured from construction steel S235, with a minimum yield strength 235 MPa and a minimum tensile strength 370 MPa.
Hot-dip galvanizing with a minimum of 50 µm.

73501	Post foot U-type 50x40	73519	Post foot adjust. 90-150, adjust. leg 240-290
73502	Post foot U-type 50x60	73520	Post foot U-type 140x90
73503	Post foot U-type 75x40	73521	Post foot adjust. 80-120 with sole (leg 115-165)
73504	Post foot U-type 75x60	73522	Post foot, adjust. 80-160
73506	Post foot U-type 90x90	73523	Post foot adjust. 70-105, adjust. leg 240-290
73507	Post foot U-type 100x40	73524	Post foot L-type 84x90
73508	Post foot U-type 100x60	73525	Post foot U-type 45x40
73509	Post foot U-type 100x90	73527	Post foot U-type 48x40
73511	Post foot U-type 120x70	73531	Post foot U-type 50x40
73512	Post foot U-type 120x90	73532	Post foot U-type 100x6
73513	Post foot U-type 125x90	73535	Post foot U-type 80x60
73514	Post foot U-type 150x60	73551	Post foot U-type 90x90
73515	Post foot L-type 70x60	73552	Post foot U-type 100x70
73516	Post foot I-type 90x60	73553	Post foot adjust. 80-100 with sole (leg 115-165)
73517	Post foot, adjust. 70-120	73554	Post foot adjust. 80-110 with sole (leg 115-165)
73518	Post foot adjust. 105-160 with sole (leg 115-185)		

Signed on behalf of the distributor by:



Henry-Stiven Villem
CEO