

24.09.2025

## DECLARATION OF CONFORMITY Nr. 2025-28

The following products are manufactured from construction steel S235, with a minimum yield strength 235 MPa and a minimum tensile strength 370 MPa. Hot-dip galvanizing with a minimum of 50 µm.

- 73801** Post foot 50x50 l=150 with ground plate, type B
- 73802** Post foot 50x100 l=150 with ground plate, type B
- 73803** Post foot 75x75 l=150 with ground plate, type B
- 73804** Post foot 90x90 l=150 with ground plate, type B
- 73805** Post foot 100x100 l=150 with ground plate, type B
- 73806** Post foot 120x120 l=150 with ground plate, type B
- 73807** Post foot 140x140 l=200 with ground plate, type B
  
- 73901** Drive-in post support 50x50mm, L=600mm, type A
- 73902** Drive-in post support 50x100mm L=750mm, type A
- 73903** Drive-in post support 75x75mm, L=750mm, type A
- 73904** Drive-in post support 100x100mm, L=750mm, type A
- 73905** Drive-in post support 90x90mm, L=750mm, type A
- 73906** Drive-in post support 95x95mm, L=750mm, type A
- 73911** Circular drive-in post support 80mm, L=750mm, type A
- 73912** Circular drive-in post support 100mm, L=750, type A
  
- 73915** Screw-in post support 50x50, L=650mm
- 73916** Screw-in post support 100x100, L=750mm
- 73917** Screw-in post support 50x100, L=750mm
- 73918** Screw-in post support 75x75, L=750mm
- 73931** Post foot 70-105 adjust. /screw-in L=750mm

Signed on behalf of the distributor by:



**Henry-Stiven Villem**  
CEO